


The ideal finish for your toilet mounting frame

The VIDI®board-PRO toilet panel is universally applicable on any toilet mounting frame. The toilet panel is equipped with recesses for drainage, supply and fastening. Despite its low weight, the toilet panel is very stable and load-bearing. The toilet panel is also the ideal substrate for all types of tiling, because the panel has a reinforcing membrane on both sides in a special mortar coating. The VIDI®board-PRO toilet panel is available in 3 sizes and can be adapted to the chosen toilet casing.



- 1 Cut or saw the toilet panel to the required size. Use a knife, multitool, handheld circular saw or jigsaw.

Corresponding fitting plates (PRO-PPK 20 and PRO-PPL 20) are available for each toilet panel size, for quick and secure finishing of the top or side of the toilet conversion.



- 2 Use a knife or multitool to cut or saw a suitable cut-out for the control panel in the correct position.



- 3 Use VIDI®fix sealant and adhesive to glue the toilet panel to the mounting frame.



- 4 Then mechanically fasten the plate with the screws and rosettes provided. Mount the screws at a sufficient distance from the edge. Screw them in until the tops of the rosettes are flush with the surface of the toilet panel.



- 5 Glue and affix the side and top panels at all the joints with VIDI®fix sealant and adhesive.



- 6 Before applying the tile adhesive, apply self-adhesive tissue mesh tape (PRO-WGB 100) to all joints and seams. Ensure a dust-free surface.



- 7 DO NOT prime the toilet plate; after the reinforcement has been applied, it can be tiled without further prior treatment. Note: if a tile size smaller than 15 x 15 cm is used, please contact us for additional advice. Always use cement-based powder glue for non-absorbent shard tiles. In consultation with the adhesive supplier, it is possible to switch to paste adhesive in the case of absorbent shard tiles. Carefully follow all the processing instructions for the adhesive and grouting materials. The toilet bowl can only be installed once the tile adhesive and grouting mortar have hardened. If you have any doubts or questions, please contact one of our advisors.



Alongside the product warranty, VIDI®board-PRO also offers a system guarantee on construction, sealing and adhesion. Please contact one of our advisors for information and advice: +31 (0)570 50 38 30 or by email on info@vidiboard.nl